

PERIMETER/SECURITY FENCING



EXAMPLE PERIMETER/SECURITY FENCING



EXAMPLE PERIMETER/SECURITY FENCING



EXAMPLE PERIMETER/SECURITY FENCING

NOTE:

1. PERIMETER FENCING MAY BE INSTALLED AROUND THE PERIMETER OF THE PROJECT OR AS OTHERWISE APPROVED BY THE PLANNING DIRECTOR AT THE TIME OF SITE PLAN REVIEW AND APPROVAL. THE DESIGN AND FINAL LOCATION FOR THE PERIMETER FENCING AND SECURITY FENCING SHALL BE APPROVED BY THE PLANNING DIRECTOR FOR CONSISTENCY IN THE CONCEPT PLAN AT THE TIME OF SITE PLAN REVIEW AND APPROVAL.
2. FENCING WILL BE A MINIMUM OF 6 FEET IN HEIGHT AND A MAXIMUM OF 7 FEET.
3. FENCING IMMEDIATELY ADJACENT TO PUBLIC OR PRIVATE STREETS SHALL NOT BE CHAIN-LINK, WITH OR WITHOUT SLATED INSERTS, AND SHALL NOT INCLUDE BARBED WIRE OR OTHER SIMILARLY VISIBLY INTRUSIVE DETERRENCE DEVICE.
4. SECURITY FENCING SHALL BE USED AROUND THE PERIMETER OF ANY SUBSTATION (UNLESS PROHIBITED BY DOMINION POWER), UNLESS OTHERWISE APPROVED BY THE PLANNING DIRECTOR AT THE TIME OF SITE PLAN REVIEW AND APPROVAL.
5. THE IMAGES ARE REPRESENTATIVE FENCING STYLES THAT WILL BE USED AS PERIMETER AND SECURITY FENCING THROUGHOUT THE PROJECT SITE.